

Fox Electronics Headquarters
5570 Enterprise Parkway
Fort Myers, FL. 33905 USA
Tel: 888-GET-2-FOX
Outside US: +1.239.693.0099
Fax: +1.239.693.1554

Fox Electronics EMEA
14 Banks Road
Biggleswade, Bedfordshire
SG18 0DY, United Kingdom
Tel/Fax: +44.1767.312632

Fox Electronics Asia
4/F Gold & Silver Commercial Bldg.
12-18 Mercer St.
Central, Hong Kong
Tel: +852.2854.4285
Fax: +852.2854.4282

Fox Electronics Japan
3-28-6-1A Yoyogi
Shibuya-ku, Tokyo 151
Japan
Tel: +81.3.3374.2079
Fax: +81.3.3377.5221

Materials Declaration

Company Name : Fox Electronics
Address : 5570 Enterprise Parkway
: Ft Myers FL 33905
Phone : 239-690-2238
Fax : 239-690-3438
E-mail : brucec@foxonline.com
Completed by Bruce Clark

Date : September 25, 2005

Product Family : NC26 - 2x6mm Crystal

| | Material Name | Component | Content (mg) | Content (w t %) | (CAS Number) |
|--------------|---------------|--------------------------------------|---------------|-------------------|--------------|
| Cover | Nickel Silver | Copper (Cu) | 13.658 | 29.80% | 7440-50-8 |
| | | Nickel (Ni) | 3.713 | 8.102% | 7440-02-0 |
| | | Zinc (Zn) | 3.938 | 8.593% | 7440-66-6 |
| | | Iron (Fe) | 0.002 | 0.004% | 7439-89-6 |
| | | Manganese (Mn) | 0.028 | 0.061% | 7439-96-5 |
| | Plating | Nickel (Ni) | 5.000 | 10.910% | 7440-02-0 |
| Base | Glass | Silica Amorphous (SiO ₂) | 2.750 | 6.0% | 7631-46-1 |
| | Kovar | Iron (Fe) | 1.898 | 4.14% | 7439-89-6 |
| | | Nickel (Ni) | 1.021 | 2.23% | 7440-02-0 |
| | | Cobalt (Co) | 0.598 | 1.305% | 7440-48-4 |
| | Alloy42 | Iron (Fe) | 3.544 | 7.733% | 7439-89-6 |
| | | Nickel (Ni) | 2.505 | 5.466% | 7440-02-0 |
| | Plating | Copper (Cu) | 0.083 | 0.18% | 7440-50-8 |
| | Plating | Lead (Pb) | 1.505 | 3.284% | 7439-92-1 |
| | | Tin (Sn) | 1.273 | 2.778% | 7440-31-5 |
| Crystal | Crystal | Silicon Dioxide (SiO ₂) | 2.360 | 5.15% | 14808-60-7 |
| | Electrode | Silver (Ag) | 0.0290 | 0.0633% | 7440-22-4 |
| | | Chromium (Cr) | 0.0020 | 0.004364% | 7440-47-3 |
| | Solder | Silver (Ag) | 0.09600 | 0.209470% | 7440-22-4 |
| | | Tin (Sn) | 1.827000 | 3.986472% | 7440-31-5 |
| TOTAL | | | 45.830 | 100.00% | |